



One of the best choice for all jointing concerns in terms of bonding different construction materials is this NUFIX Jointing Mortar. The adhesive chattels of this jointing mortar is very high and shows strong bonding between materials. It is suitable for interior and exterior construction materials. Assures good quality and leaves no stains behind. It is also effective on parapet walls, cement windows and doors. It also acts as a good bonding agent for boundaries and garden walls.

- It is a good pick for effective adhesive works.
- Trouble-free processing.
- Easy application and easy drying.
- No soaking or curing of the block is required.

Uses

- Nufix Jointing Mortar be used to joint AAC Bricks, Cement Bricks and Conventional Bricks
- It is easy to use, being premixed and also ensure the compaction of interlocking bricks. Making bonds together and more durable
- No seepage / water percolation through joints because of better bonding joints
- No question of formation of efflorescence

Application Procedure

- Prepare the surface by cleaning all dust and make the surface slightly moist using water
- Mix the power with water by hand or stirred until there are no lumps and mix is uniform
- Use one mug water for two mugs of powder
- Apply the mixed material with trowel 3 to 4 mm thickness
- Use the material within 120 min of mixing

Storage

Nufix Jointing Mortar is available in 40 kg bag. Stocking life is 6 months. The product should be kept in covered and dry place.

“Specially created to enhance the ease of working, improve the adhesion as compared to the conventional adhesives and improve the strength”

Technical Data Specifications :

Water Demand	Approx. 21% or 8.4 Liters /40 kg Bag
Form	Dry Powder
Coverage	Approx 1.2 Cu.mt (or) 80 to 90 sq.ft surface area per 40 kg bag
Bed thickness	Approx 3-4 mm
Pot Life	Approx 60-120 min
Curing	Self Curing (No additional curing required)
Tensile Adhesion Strength	0.55-1.0 N/Sq.mm as per ASTM 4541 on AAC Block after 28 days
Compressive Strength	>4N/mm ² as per IS 4031 part 6
Colour	Grey

Note: Technical data sheet is for general information only. NUGEL Industries Private Limited has the right to modify the contents of the data sheet any time.

