



It is not easy to switch to ready made plastering mix leaving the traditional plastering method behind. NUFIX ready wall plaster has a lasting impact on this changeover with its high quality. It has very good bonding properties that adheres to the base very strongly. The surface appears smooth and classy. It is suitable for different plastering substrates such as AAC blocks, CLC blocks and cement bricks. It can be efficiently used on bricks, blocks and concrete walls. The extra benefit is that it can also be used on inner and outer walls.

- An improved and assured quality and reliability
- Can operationally replace traditional plastering method.
- Adheres to the base strongly and gives smoothness on the surface.
- Requires minimal effort for mixing and application.

Uses

- It can be used on inner and outer walls
- It can be also used efficiently on bricks, blocks concrete walls
- Instead of traditional plastering Ready Wall Plaster can be used
- It is easy to apply, stronger, surface looks smooth and good bonding to its base
- Time saving and least rebound and less curing
- We are using quality and graded sand does not contain silt and dirt, so finally won't form cracks & will get very good finishing.

Application Procedure

- Prepare the surface by cleaning all dust and make the surface slightly moist using water
- Mix 5 kgs of powder with 2 ltrs of water (Appr.) and stir until we get uniform mix
- Apply the mixed material 6 mm to 12 mm thickness
- Use the material within 60 mins of mixing
- For better result, cure the wall with water 2 to 3 times per day for 7 days

“This wall plaster has been created in order to replace the conventional plaster of cement and sand that is mixed at the site of the gypsum plaster for that matter”

Technical Data Specifications :

Form	Dry Powder
Coverage	40-60 Sq.ft / 40 kg bag at 6-10 mm
Colour	Grey
Thickness	6-12 mm
Pot Life	Approx 120 minutes at 30°C
Compressive Strength	> 4 MPa after 28 days
Curing	Water 2-3 times a day for 7 days
Bulk Density	Approx. 1.8 Kg / ltr
Water Demand	Approx 20% or 8 litres / 40 kg bag

Storage

Nufix Ready Wall Plaster is available in 40 kg bag. Stocking life is 6 months. The product should be kept in covered and dry place.

Note: Technical data sheet is for general information only. NUGEL Industries Private Limited has the right to modify the contents of the data sheet any time.

