



NUFIX Tile Adhesive material is formulated uniquely to fix tiles. It is also suitable for fixing different construction materials in interiors and exteriors. It has a high work ability and thus makes the application very easy. It provides an intact impermeable layer so that the surface is protected from wet conditions. To accommodate normal floor movements this tile adhesive provides a good range of flexibility. It is very important to take precautionary methods by avoiding wet tiles before fixing. It does not leave any stains on the tiles hence giving a fine finishing to the surface.

- A water and frost resistant adhesive.
- Can easily survive in areas with high static and thermic stress.
- Does not lose its quality on prefabricated concrete, terraces, swimming pools and facades.
- Stain or victual proof.

## Uses

- Nufix Tile Adhesive is a high strength especially design for wall and floor tiling
- Ideal for all kinds of tiles including granite, marble and ceramic tiles
- Ready to use after mixing with sufficient water
- It works fine for both damp and dry conditions for various kinds of substrates.
- It can be used for all kinds of surfaces.

## Storage

Nufix Tile Adhesive is available in 40 kg bag. Stocking life is 6 months. The product should be kept in covered and dry place.

## Technical Data Specifications :

Colour	Grey
Water demand	Approx. 25%
Density	Approx 1.5 g/cc
Consumption	1.2 Kg/m <sup>2</sup> /mm
Self Curing	No additional curing is required
Bed Thickness	3-4 mm
Coverage	120 sft/40 kg Bag Approx
Pot Life	120 minutes

## Usage Instructions :

- Prepare the surface by cleaning all dirt / dust and make the surface slightly moist using water
- Add sufficient quantity of water to tile adhesive to make homogeneous paste.
- Let the mixture stand for 10 minutes to give enough time for the additives to dissolve. After 10 minutes, mix it well. The mixture is ready for use.
- Apply the mixed material with trowel 2 to 3 mm thickness
- Take the tile and press it firmly onto the surface such that it gets locked into place.
- It is very important to ensure that the fresh mortar covers the backside of the whole tile.
- Use the material within 120 min of mixing.

**Note:** Technical data sheet is for general information only. NUGEL Industries Private Limited has the right to modify the contents of the data sheet any time.

***“Dry set adhesive boasts of a high quality and has been specifically blended for laying thin ed tiles on the walls and the floors”***

